

## Agilent 1100 Series HPLC



Agilent 1100 Series HPLC

Rating: Not Rated Yet

**Price**

Sales price \$24,500.00

[Ask a question about this product](#)

Manufacturer [Agilent](#)

### Description

This Agilent 1100 is a complete HPLC system with Binary pump, Diode Array Detector, Degasser with solvent tray, Column Compartment, including PC (not pictured) & licensed ChemStation software.

Note: other HPLC module combinations available (Capillary Pump, Multiple Wavelength Detector, Thermostated Column Compartment, see other listings for individual modules)  
 ALS Autosampler G1329A specifications -

Type	Specification
GLP Features	Early maintenance feedback (EMF), electronic records of maintenance and errors
Communications	Controller-area network (CAN), GPIB (IEEE-488), RS232C, API-compatible standard, optional four external contact closures and BCCD vital number counter
Safety Features	Leak detection and safe leak handling, low voltages in maintenance areas, motor detection and display
Injection range	1 - 100 µl in 0.1 µl increments up to 1500 µl with multiple draw hardware modification (required)
Replicate injections	1 - 99 from one vial
Precision	Typically < 0.5 % RSD of peak areas from 5 - 100 µl. Typically < 1 % RSD of peak areas from 1 - 5 µl
Minimum sample volume	1 µl from 5 µl sample in 100 µl microvial, or 1 µl from 10 µl sample in 500 µl microvial
Carryover	Typically < 0.1 % < 0.05 % with external needle cleaning
Sample viscosity range	0.1 - 50 cP
Replicate injections per vial	1 - 99
Sample capacity	100 x 2-ml vials in 1 tray 80 x 2-ml vials in 1/2 tray 15 x 6-ml vials in 1/2 tray (Agilent vials only)
Injection cycle time	Typically 60 s depending on draw speed and injection volume

### Diode Array Detector G1315B Features:

Features:  
 Access the spectral domain with superior 3D optics-simultaneous illumination using combined deuterium and tungsten lamps for highest intensity and lowest detection limit from 190 to 950 nm, 1024 diodes and 1-cm slit for highest spectral resolution.  
 Programmable slit helps you explore the spectral landscape for better sample characterization-focus on fine bands with narrow setting, or if higher sensitivity is required open up the programmable slit for more light throughput. A broad slit ensures lowest baseline noise and highest chromatographic signal-to-noise. Store and report slit settings, from 1 - 16 mm, together with your raw data for GLP traceability.  
 Spectral range and flexible viewing - easily overlaid spectra within a set of between runs.  
 Verify wavelength accuracy for GLP compliance-automatic holmium oxide filter (which can be set at the beginning of your chromatography) verifies that your wavelength is indeed what the setpoint says it is.

### Degasser G1379A Specifications -

Type	Specification
Maximum flow rate	0.8 ml/min per channel 5-10 ml/min per at reduced degassing performance

Number of channels	2
Internal volume per channel	Typically 12 µl per channel
Materials in contact with solvent	PTFE, PEEK

Biotech Equipment Sales, Inc.  
226 Miller Ave.  
South San Francisco, CA 94080  
650-871-5707 office  
650-276-7487 fax  
[sales@biotechequipmentsales.com](mailto:sales@biotechequipmentsales.com)